

Ref.: 365316



PRESET DIGITAL METERED CONTROL VALVE, PCP30 SERIES, 30 L/MIN, 60° RIGID OUTLET, QUARTER TURN

SAMOA control valves are used at the end of hose assembly to dispense lubricants and antifreeze solutions. · Electronic meter with pre-set function. · Hands-off operation: meter automatically shuts off once the preset volume is delivered. · With large LCD display and high flow inlet swivel. · Works with easy to replace "AA" alkaline batteries. · Liters, Gallons, Quarts, Pints · Model with 60° rigid outlet and quarter turn. Instruction book: 896846.

Technical data

Documentation

More information

Compatible fluids	Oil, Transmission fluid, Coolant
Maximum free flow delivery	30 l/min (8 gal/min)
Accuracy	0.005
Maximum outlet pressure	100 bar (1450 psi)
Operating temperature range	-10 - 50 °C (14-122 °F)
Inlet size	1/2"
Fluid inlet	1/2" BSP (F)
Fluid outlet	1/2" BSP (F)
Outlet type	60° rigid tube, quarter turn manual tip
Meter	Preset digital
Metric	Litres, Gallons, Pints, Quarts
Wetted materials	Aluminium, Steel, Stainless steel (AISI 316), NBR, Acetal, Brass, Zinc plated steel
Weight	2,19 kg (4,8 lb)

Technical data

Documentation

More information

Instruction manuals

896846 Instruction book: Preset digital metered control valve, PCP30 series, 30 l/min, no outlet (PDF)

[Download](#)

Catalogs

Product brochure: PRESET GUN, 2022 EN (PDF)

[Download](#)

Product brochure: PRESET GUN, 2022 EN (PDF)

[Download](#)

Product catalogue: GENERAL EXPORT, 2024 EN (PDF)

[Download](#)

Spare parts

Spare part document: PCP3001 365310 (PDF)

[Download](#)

Models

Code	Compatible Fluids	Inlet Size	Outlet Type
365316	Oil, Transmission fluid, Coolant	1/2"	60° rigid tube, quarter turn manual tip
365317	Oil, Transmission fluid, Coolant	1/2"	Formable tube, quarter turn manual tip
365310	Oil, Transmission fluid, Coolant	1/2"	No outlet