

With double hydraulic cylinders and high strength chain drive, the lift tools guarantee stable and smooth lifting and lowering. The patented slider bracket design improves the replacing efficiency. All are CE certificated to meet the demand of the garages and workshops.



## Features

- Bilateral manual safety unlocking system.
- The cable and oil pipe are fully concealed, with decent and elegant appearance.
- Wire rope equalization system forces synchronous movement of two carriages and effectively prevents vehicle from tilting.
- 24V low voltage control box(IP54 level)ensures operator's safety.
- 24V cylinder travel limit switch effectively protects cylinder and extends its lifespan.
- Door rubber pad protects car door from being damaged in collision.
- More lifting pads with different height meets the requirements for light lorries and SUVs.
- CE certificated and passed 115% dynamic loading test and 150% static loading test.
- Symmetric and asymmetric installation types are optional. (For SC model)

## Specifications

### OPTIONAL PARTS

	<b>TLT240SB</b>	<b>TLT240SC</b>
<b>CAPACITY (KG)</b>	4000	4000
<b>LIFTING HEIGHT (MM)</b>	1920	1920
<b>INITIAL HEIGHT (MM)</b>	110	110
<b>LIFTING TIME (S)</b>	≤55	≤55
<b>LOWER TIME (S)</b>	≥20 ≤40	≥20 ≤40
<b>PASSING WIDTH FOR SYMMETRIC INSTALLATION (MM)</b>	2486	2486
<b>PASSING WIDTH FOR ASYMMETRIC INSTALLATION (MM)</b>	-	2415
<b>OVERALL WIDTH FOR SYMMETRIC INSTALLATION (MM)</b>	3370	3420
<b>OVERALL WIDTH FOR ASYMMETRIC INSTALLATION (MM)</b>	-	3563
<b>OVERALL HEIGHT (MM)</b>	2860	3840
<b>MOTOR POWER (KW)</b>	2.2	2.2
<b>MOTOR VOLTAGE</b>	3 phase/380V or single phase/220V	
<b>WORKING NOISE (DB(A))</b>	≤75dB	≤75dB
<b>WORKING OIL PRESSURE (MPA)</b>	18	18

90mm square low lifting tray accessory (adjustment range:25-90mm)	Extension sleeve 90/125/140mm
	