



Our mobile, unheated HD 6/15 M Plus high-pressure cleaner comes with numerous innovative equipment features as standard for safe and comfortable working. The automatic pressure relief feature protects high-pressure components from loads in stand-by mode, for example, while the innovative EASY!Force high-pressure gun utilises the recoil force of the high-pressure jet to reduce the retaining force to zero, and the EASY!Lock quick-release couplings enable handling that is five times faster than conventional screw connections, without compromising on robustness or longevity. The machine is suitable for vertical or horizontal operation and thus offers a great deal of flexibility in use. The robust 3-piston axial pump with brass cylinder head increases cleaning power and energy efficiency by around 20%. Numerous options for stowing and storing accessories so that they are safe for transportation and a very service-friendly machine design round off the sophisticated concept of the HD 6/15 M Plus.

Features

Clever accessory storage

- Holder for the cup foam lance.
- EASY!Lock TR20 permits storage of the Power nozzle or a surface cleaner directly at the machine.
- Practical nozzle compartment for storing the rotary nozzle.

Easy servicing

- Easy access to the cylinder head through the open part at the bottom of the machine.
- Quick access to the electrical box by simple removal of the machine cover.
- Large, easy-to-reach water fine filter for protecting the pump against dirt particles in the water.

Effortless and time-saving solutions

- Fatigue-free EASY!Force high-pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five times faster than screws.

Increased energy efficiency

- Newly developed 3-piston axial pump with considerably reduced flow and pressure losses.
- 20% increase in cleaning performance and energy efficiency.

Specifications

- Supply voltage (Ph/V/Hz) 1 / 230 / 50
- Flow rate (l/h) 560
- Inlet temperature (°C) 60
- Working pressure (bar/MPa) 150 / 15
- Max. pressure (bar/MPa) 225 / 22,5
- Connected load (kW) 3,1
- Power cable (m) 5
- Water inlet 3/4"
- Weight (with accessories) (kg) 30
- Weight incl. packaging (kg) 33,5
- Dimensions (L x W x H) (mm) 400 x 455 x 700