



Ref.: 167500

## HAND HELD AIR OPERATED GREASE GUN, 1000 CC, FLEXIBLE OUTLET

1.000 cc air operated grease pump. Includes a 1.000 cc barrel with an air driven grease follower. Recommended for high viscosity grease and low temperatures. Supplied with 400 mm double steel braid reinforced outlet hose with 4 jaw connector (PN 140 040) and filler nipple. Bulk grease loading using a grease filler pump. High pressure, 60:1 pressure ratio, air operated grease pumps. They can be connected to a compressed air line or to the air brake circuit of a commercial vehicle. Delivery: 1 cc each time the trigger is pressed. Maximum air pressure: 10 bar. Air connection thread 1/4" BSP (F). Instruction book: 816801.

### Technical data

### Documentation

### More information

<b>Compatible fluids</b>	Grease
<b>Operation type</b>	Hand Held Air Operated Pumps
<b>Maximum outlet pressure</b>	10 bar (145 psi)
<b>Delivery</b>	1 cc (0.03 oz)
<b>Reservoir capacity</b>	1000 cc (34 oz)

### Technical data

### Documentation

### More information

## Instruction manuals

816801 Instruction book: Hand held air operated grease gun, 1000 cc, flexible outlet (PDF)

[Download](#)