

Ref.: 413081



CONTROL VALVE, PG-77/F SERIES, 1 KG/MIN, GREASE, REINFORCED HOSE OUTLET

High pressure grease control guns with ergonomic body and trigger designed to reduce operator hand fatigue. Manufactured in aluminium with steel insert for high pressure. 450 mm double steel braid reinforced rubber hose with 3 jaw connector
 Instruction book: 841801.

Technical data

Documentation

More information

Compatible fluids	Grease
Maximum free flow delivery	1 kg/min (2,2 lb/min)
Maximum outlet pressure	500 bar (7250 psi)
Operating temperature range	-10 - 70 °C (14-160 °F)
Inlet size	1/4"
Fluid inlet	1/4" BSP (F)
Fluid outlet	1/8" BSP (F)
Outlet type	Reinforced tube, grease connector
Meter	No meter
Wetted materials	Zinc plated steel, Steel, Rubber
Weight	0,97 kg (2,14 lb)

Technical data

Documentation

More information

Instruction manuals

841801 Instruction book: Control valve, PG77 series, 1 kg/min, grease (PDF)

[Download](#)

Catalogs

Product catalogue: GENERAL EXPORT, 2024 EN (PDF)

[Download](#)

Spare parts

Spare part document: PG7701 413077 (PDF)

[Download](#)

Models

Code	Compatible Fluids	Inlet Size	Outlet Type
413081	Grease	1/4"	Reinforced tube, grease connector
413082	Grease	1/4"	Z-swivel, reinforced hose tube, grease connector
413080	Grease	1/4"	Z-swivel, rigid tube, grease connector
413077	Grease	1/4"	Rigid tube, grease connector