

HG 64

With our HG 64 hot water generator (64 kW heat output), you can cost-effectively transform any cold water high-pressure cleaner into a hot water machine with higher cleaning performance.



Order no. 1.030-510.0

Technical data

EAN code		4054278262628
Heating output	kW	64
Temperature (for supply 12 °C)	°C	max. 80
55 °C Δ T @	l/h	900
Weight without accessories	kg	124.2
Weight incl. packaging	kg	136.6
Dimensions (L × W × H)	mm	1000 × 850 × 1080



Durable and robust

- Highly efficient, tried-and-tested "Made in Germany" burner technology.
- Tried-and-tested Kärcher safety technology guarantees optimal protection of the machine and user.
- The sturdy pipe frame provides protection in continuous heavy-duty use.



Increased cleaning performance thanks to hot water

- Shorter cleaning times and reduction of labour costs.
- More effective removal of oils, greases and lubricants.
- Germ-killing effect and protection of sensitive surfaces.



Especially easy to maintain

- Easy access to all service and maintenance components.
- Integrated fuel filter and removable fuel tank for cleaning.

ACCESSORIES FOR HG 64

1.030-510.0



		Order no.	Description	
TRIGGER GUNS				
Spray guns				
M22 Classic spray gun	1	4.760-843.0	High-quality Classic spray gun with robust valve. Also suitable for Kärcher hot water high-pressure cleaners.	■
Pistol TR 155°C with package	2	4.119-002.0		□
EASY!Force Advanced	3	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	□
EASY!Force conversion kit 2 - from machine	4	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	□
SPRAY LANCES				
Spray lance				
Spray lance 850 mm	5	9.751-044.0	The 600-mm long galvanised spray lance with hand screw connection is suitable for machines in the HD Classic range. The spray lance is not rotatable.	■
Spray lance Classic 1,050 mm	6	4.760-855.0	High-pressure spray lance with M 22 screw connections from the Classic series from Kärcher. Also suitable for hot water high-pressure cleaners.	□
Jet pipe 600mm with package	7	4.760-856.0		□
Jet pipe Classic M 200mm	8	4.760-887.0		□
Jet pipe Classic M 400mm	9	4.760-888.0		□
Jet pipe Classic M 840mm	10	4.760-895.0		□
250 mm lance, non-rotatable	11	4.760-667.0	250 mm stainless steel lance. With manual coupling. Non-rotatable.	□
550 mm lance, non-rotatable	12	4.760-665.0	550 mm stainless steel lance. With manual coupling. Non-rotatable.	□
Rotating spray lances				
Spray lance, 600 mm, rotatable	13	4.760-664.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Spray lance, 840 mm, rotatable	14	4.760-663.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR HG 64

1.030-510.0



		Order no.	Description	
SPRAY LANCES				
Rotating spray lances				
Spray lance, 1050 mm, rotatable	15	4.760-660.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 1550 mm, rotatable	16	4.760-661.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 2050 mm, rotatable	17	4.760-662.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Angular spray lance				
Spray lance for toilets and rain gutters	18	4.760-073.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	☐
Flexible spray lance				
High pressure articulated joint	19	4.481-039.0	High-pressure articulated joint: Thanks to infinite angle adjustment up to 120°, this tool is ideal to effortlessly clean hard-to-reach areas. Simply attach to the spray lance of the pressure washer.	☐
Jet pipe flexible 0.85m, 850 mm	20	6.394-655.0	1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	☐
Flexible lance, 1050 mm	21	6.394-654.0		☐
Undercarriage spray lance				
Underbody lance	22	4.760-245.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	☐
WEED CONTROL				
WR 50	23	2.643-758.0	In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	☐
WR 20	24	2.643-760.0	For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	☐
QUICK CONNECT				
Quick coupling	25	6.401-458.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	☐
Male coupling	26	6.401-459.0	Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22 × 1.5 external thread.	☐
DRUM AND TANK CLEANING				
Add-on kit mud sucker	27	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	☐
SEALS FOR TRAPEZOIDAL THREAD				
Gasket set with 9x O-rings for TR thread	28	2.880-001.0		☐

☐ Available accessories.

ACCESSORIES FOR HG 64

1.030-510.0



		Order no.	Description	
STEAM JET NOZZLE / NOZZLE PROTECTOR / ROLLOVER NOZZLE				
Rollover nozzle holder				
Owner of jets double brass	29	4.764-012.0	Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle).	☐
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 30 m, ID 8, 315 bar, 2 x M22 x 1.5	30	6.390-293.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5.	☐
High-pressure hose, 15 m, ID 10, 220 bar, 2 x M22 x 1.5	31	6.390-023.0	Connectors at both ends, M 22 x 1.5, with kink protection.	☐
High-pressure hose, 20 m, ID 10, 220 bar, 2 x M22 x 1.5	32	6.390-726.0	with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar	☐
High-pressure hose, 25 m, ID 10, 220 bar, 2 x M22 x 1.5	33	6.391-513.0		☐
High-pressure hose, 15 m, ID 12, 210 bar, 2 x M22 x 1.5	34	6.391-849.0	High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 x 1.5 with anti-kink protection.	☐
High-pressure hose, 40 m, ID 12, 210 bar, 2 x M22 x 1.5	35	6.391-865.0		☐
Longlife 400				
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 1 x M22 x 1.5 / 1 x AVS-hose reel connection	36	6.390-208.0	20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced.	☐
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 x M22 x 1.5	37	6.388-083.0	10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection.	☐
High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 x M22 x 1.5	38	6.389-709.0	With rotary coupling, 2 x M 22 x 1.5	☐
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 x M22 x 1.5	39	6.390-027.0	with rotary coupling, 2 x M 22 x 1.5	☐
High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 x M22 x 1.5	40	6.390-294.0	With rotary coupling, 2 x M 22 x 1.5	☐
Longlife food design with screw connections at both ends				
High-pressure hose food grade, 10 m, ID 8, 400 bar, 2 x M22 x 1.5	41	6.391-864.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5	☐
Special hoses				
High-pressure hose curved, 1.5 m, ID 8, 400 bar, 2 x M22 x 1.5	42	6.388-886.0	Connection hose in longlife quality with 2x M22 x 1.5, with angled connection on one side.	☐

☐ Available accessories.

ACCESSORIES FOR HG 64

1.030-510.0



		Order no.	Description	
HIGH-PRESSURE HOSES				
Classic				
Hose assembly with package M22 DN10 25MP, 20 m, ID 10, 250 bar × , M22 × 1.5	43	4.760-892.0	High-pressure hose with M22 screw connections from the Classic series from Kärcher. Also suitable for hot water high-pressure cleaners.	☐
FLOOR AND HARD SURFACE CLEANER				
FR 30 Me surface cleaner				
Hard surface cleaner FR 30 Me	44	2.640-355.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	☐
FRV 30 Me surface cleaner				
FRV 30 Me	45	2.642-911.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	☐
Extension hose FRV 30 Me and FRV 50 Me	46	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	☐
FOAM SYSTEMS				
Inno Foam Kit				
Inno Foam Set with detergent injector	47	2.640-151.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	☐
Inno Foam Set	48	2.640-692.0		☐
Easy Foam Set				
Easy Foam Set with RM injector	49	2.640-691.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	☐
Easy Foam Set	50	2.640-693.0		☐
Cup foam lance				
1-litre cleaning agent container for cup foam lance basic	51	5.071-414.0	For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0).	☐
1-litre cleaning agent container for cup foam lance advanced	52	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	☐
COUPLING PARTS				
Rotary coupling				
Rotary coupling	53	4.401-091.0	Reliably prevents twisting of HP hoses. Connection M 22 × 1.5 m. Handle protection	☐
Coupling				
Coupler -2 × M22 × 1,5	54	4.403-002.0	For connecting and extending high-pressure hoses. Connection 2 × M 22 × 1.5.	☐
Connector				
Y distributor	55	4.405-048.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	☐
	56	4.111-024.0		☐

☐ Available accessories.

ACCESSORIES FOR HG 64

1.030-510.0



		Order no.	Description	
COUPLING PARTS				
Adapters				
Sealing cone complete	57	4.424-004.0	In order to install high-pressure hose with male coupling on thread with M22 x 1.5 Alternative: 4.111-032.0 Adapter 4 – Device new / Hose old Swivel	☐
EASY!Lock adapter				
Adapter 1 M22AG-TR22AG	58	4.111-029.0	Adapter 1 to connect the old hose with the new hose	☐
Adapter 2 M22IG-TR22AG	59	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	☐
Adapter 3 M22IG-TR22AG	60	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	☐
Adapter 5 TR22IG-M22AG	61	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	☐
Adapter 6 TR22IG-M22AG	62	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	☐
Adapter 7 M18IG-TR20AG	63	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	☐
Adapter 8 TR20IG-M18AG	64	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	☐
Adapter 12 rotary coupling EASY!Lock 22 IG – M22 x 1.8 AG	65	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	☐
HOSE REELS				
Automatic, self-winding hose reels for wall mounting				
Automatic stainless steel hose reel, 20 m	66	6.391-520.0		☐
Automatic stainless steel hose reel, 40 m	67	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	☐
Zinc-coated swivel holder	68	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	☐
Stainless steel swivel holder	69	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	☐
Automatic plastic hose reel incl. high-pressure hose, 15 m	70	2.639-257.0	Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety.	☐

☐ Available accessories.

ACCESSORIES FOR HG 64

1.030-510.0



		Order no.	Description	
HOSE REELS				
Automatic, self-winding hose reels for wall mounting				
Automatic hose reel, powder-coated steel / plastic, 20 m	71	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	☐
Automatic stainless steel / synthetic material hose drum, 20 m	72	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	☐
Automatic hose reel, coated, 20 m	73	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	☐
Hose reel, automatic, basalt grey-coated, 20 m	74	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	☐
Automatic hose reel, stainless steel, includes swivel holder, 20 m	75	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	☐
WATER CONNECTION				
Geka coupling				
Geka connector with hose barb, R 3/4"	76	6.388-455.0	with hose liner	☐
Geka connector with hose barb, R 1"	77	6.388-465.0	with hose barb	☐
Geka connector with internal thread, R 1"	78	6.388-458.0	with female thread	☐
Suction filter				
Water suction filter	79	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	☐
Suction filter with check valve	80	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	☐
Water fine filter				
Universal water fine filter, 25 µm	81	2.637-020.0	Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter.	☐
Water fine filter, with adapter	82	4.730-102.0	Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	☐
Water fine filter, 100 µm, R 1"	83	2.638-270.0	Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	☐
WASHING BRUSHES				
Push-on washing brush				
Push-on wash brush	84	4.762-016.0	For general-purpose cleaning of all surfaces. Clamps directly onto the spray lance. Connection M 18 x 1.5	☐

☐ Available accessories.

ACCESSORIES FOR HG 64
1.030-510.0



		Order no.	Description	
WASHING BRUSHES				
Rotating washing brush				
Rotating wash brush for < 800 l/h machines, nylon bristles	85	4.762-561.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60°C. (M 18 × 1.5, replaceable brush insert). Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 × 1.5 (replaceable brush insert).	☐
Rotating wash brush for > 800 l/h machines	86	4.762-559.0		☐
Rotating wash brush for < 800 l/h machines, natural bristles	87	4.762-560.0		☐
Rotating wash brush for > 800 l/h machines	88	4.762-562.0		☐

☐ Available accessories.