

Ref.: 569001



## AUTOMATIC STAINLESS STEEL/ POLYPROPYLENE NOZZLE, 45 L/MIN, Ø 19 MM INLET

AdBlue/DEF nozzles with stainless steel and thermoplastic versions available. Depending on the model they can be manual or automatic, with spike or thread connection. 45 L/MIN, Ø 19 mm inlet hose barb.

### Technical data

### Documentation

### More information

<b>Compatible fluids</b>	AdBlue/DEF
<b>Maximum free flow delivery</b>	45 l/min (12 gal/min)
<b>Maximum outlet pressure</b>	5 bar (72,5 psi)
<b>Operating temperature range</b>	-20 - 55 °C (-4-131 °F)
<b>Inlet size</b>	19 mm hose barb
<b>Fluid inlet</b>	19 mm hose barb
<b>Outlet type</b>	No outlet
<b>Meter</b>	No meter
<b>Wetted materials</b>	Stainless steel, Viton, Polypropylene
<b>Weight</b>	0,9 kg (2 lb)

### Technical data

### Documentation

### More information

## Catalogs

Product catalogue: GENERAL EXPORT, 2024 EN (PDF)

[Download](#)

## Models

Code	Compatible Fluids	Inlet Size	Outlet Type
569001	AdBlue/DEF	19 mm hose barb	No outlet
569000	AdBlue/DEF	19 mm hose barb	No outlet