

Ref.: 532330



PNEUMATIC PISTON GREASE PUMP, PUMPMASTER 60, PM60 - 3:1 (KIT COMPONENT)

PM60 series air operated piston pumps. This is a component for a kit. PUMPMASTER 60, 3:1 ratio pneumatic piston grease pump. Instruction book: 853824.

Technical data

Documentation

More information

Fluids	Grease
Compatible fluids	Grease
Pump mounting	Bulk tote
Pressure ratio	3:1
Air pressure operating range	2-7 bar (29-101,5 psi)
Air consumption	2300 NL/min (81 scfm)
Maximum outlet pressure	21 bar (304,5 psi)
Air motor effective diameter	150 mm (6")
Air motor stroke	100 mm (4")
Delivery per cycle	0,774 kg (1,7 lb)
Cycles per minute (aprox.)	1.3 cycles
Delivery	40 kg/min (88 lb/min)
Maximum free flow delivery	150 kg/min (330 lb/min)
Air inlet	1/2" BSP (F)
Fluid inlet type	Chop-check
Fluid outlet	2" BSP (F)
Wetted materials	Aluminium, Steel, NBR, PTFE, Polyurethane, Viton
Pump tube material	Carbon steel
Sound level	80 dB
Tube height	164 mm (6,4")
Total height	684 mm (27")
Weight	24 kg (53 lb)

Technical data

Documentation

More information

Instruction manuals

853824 Instruction book: Pneumatic piston grease pump, Pumpmaster 60, PM60 - 3:1 (PDF)

[Download](#)

Catalogs

Product catalogue: GENERAL EXPORT, 2024 EN (PDF)

[Download](#)

Spare parts

Spare part document: PM6002 532330 (PDF)

[Download](#)