

Ref.: 569006



AUTOMATIC STAINLESS STEEL/ POLYPROPYLENE NOZZLE SPECIAL FOR PASSENGERCARS (MISS-FILLING PREVENTION), 5 L/MIN, 1" BSP (M) INLET

AdBlue/DEF nozzles with stainless steel and thermoplastic versions available. Depending on the model they can be manual or automatic, with spike or thread connection. 5 L/MIN, 1" BSP (M) inlet thread. Integrated mis-filling prevention (Elaflex).

Technical data

Documentation

More information

Compatible fluids	AdBlue/DEF
Maximum free flow delivery	10 l/min (2,6 gal/min)
Maximum outlet pressure	3,5 bar (50 psi)
Operating temperature range	-5 - 55 °C (23-131 °F)
Inlet size	1"
Fluid inlet	1" BSP (M)
Outlet type	Miss-filling prevention
Meter	No meter
Wetted materials	Aluminium, Stainless steel, NBR, Polyamide
Weight	1,5 kg (2 lb)

Technical data

Documentation

More information

Catalogs

Product catalogue: GENERAL EXPORT, 2024 EN (PDF)

[Download](#)

Models

Code	Compatible Fluids	Inlet Size	Outlet Type
569006	AdBlue/DEF	1"	Miss-filling prevention
569005	AdBlue/DEF	19 mm hose barb	No outlet