

Ref.: 684531



## 24 V DC ROTARY VANE PUMPS FOR DIESEL, POLUX SERIES, 40 L/MIN

Self priming pumps with self-adjustable vanes. Pump body made of cast-iron with rustproof treatment, rotor of sintered steel and vanes of acetyl resin. The pump includes a by-pass valve and a built in filter with easy access for cleaning. The pump can be mounted vertically or horizontally, has a carrying handle and 2 m cable with crocodile clamps. Inlet / outlet connection: 1" BSP (F) or flange coupling. Maximum suction lift: 2,5 m. Electric DC motor with IP-55 protection, allows intermittent operation duty with maximum cycles of 30 minutes. On/off switch and fuse.

### Technical data

### Documentation

### More information

<b>Compatible fluids</b>	Diesel
<b>Maximum free flow delivery</b>	40 l/min (10,6 gal/min)
<b>Delivery</b>	40 l/min (10,6 gal/min)
<b>Maximum outlet pressure</b>	0,8 bar (11,6 psi)
<b>Supply type</b>	24 V DC
<b>Current</b>	13 A
<b>Power</b>	200 w

### Technical data

### Documentation

### More information

## Instruction manuals

868809 Instruction book: 12 or 24 V DC Polux series electric pumps (PDF)


[Download](#)

### Technical data

### Documentation

### More information

mm (in)	684531
A	150 (5 25/32")
B	110 (1 9/64")
C	245 (10 53/64")
D	150 (4 21/64")
E	120 (5 29/32")
F	167 (1 13/32")
G	150 (5 29/32")
H	31 (5 29/32")



## Models

<b>Code</b>	<b>Delivery</b>	<b>Supply Type</b>	<b>Power</b>
684531	40 l/min (10,6 gal/min)	24 V DC	200 w
684530	40 l/min (10,6 gal/min)	12 V DC	170 w
684451	60 l/min (16 gal/min)	12 V DC	220 w
684450	65 l/min (17,2 gal/min)	24 V DC	240 w