



20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. M 22 x 1.5, with kink protection. Two layer high-strength steel wire reinforced. Further data: DN 8/155°C/400 bar.

Specifications

- ID 8
- Temperature (°C) max. 155
- Max. pressure (bar) 400
- Length (m) 20
- Connection thread 1 x EASY!Lock / 1 x AVS-hose reel connection
- Weight incl. packaging (kg) 6.1

Compatible Machines

- | | | |
|--|----------------------|--|
| • Automatic hose reel, coated, 20 m | • HD 7/14-4 MXA Plus | HDS 12/14-4 St Gas LPG |
| • Automatic hose reel, powder-coated steel / plastic, 20 m | • HD 7/16-4 St | HDS 6/14 CX |
| • Automatic hose reel, stainless steel, includes swivel holder, 20 m | • HD 7/17 MXA Plus | HDS 6/14-4 CX |
| • Automatic stainless steel / synthetic material hose drum, 20 m | • HD 8/18-4 MXA Plus | HDS 7/12-4 MX |
| • HD 10/21-4 SXA Plus | • HD 9/18-4 St | HDS 7/16 CX |
| • HD 10/25-4 SXA Plus | • HDC Advanced | HDS 8/17 CX |
| • HD 13/12-4 St | • HDC Classic | HDS 8/18-4 CX |
| • HD 13/18-4 SXA Plus | • HDC Standard | HDS 9/14-4 St |
| • HD 6/15 MX Plus | • HDS 12/14-4 St | HDS 9/16-4 St Gas |
| • HD 6/15 MXA Plus | • HDS 12/14-4 St Gas | Hose reel, automatic, basalt grey-coated, 20 m |