

Top Tec 6100 0W-30

Description

Motor oil based on synthetic technology. Ensures outstanding performance and a long engine service life. Improves the viscosity, lowers friction and reduces fuel consumption. Additives with a much lower proportion of ash-forming substances provide optimal protection for the diesel particulate filter from dirt. Keeps sensitive engine components clean.

Properties

- excellent cold-start behavior
- ensures maximum engine performance
- highest fuel economy
- extremely low oil consumption
- excellent wear resistance
- ensures a long engine life
- high engine cleanliness
- very good temperature stability
- engine components are kept clean and given excellent protection
- contains much lower fractions of ash-forming substances
- tested for turbochargers and catalytic converters

Specifications and approvals:

ACEA C2 • BMW Longlife-12 FE

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

BMW 83 21 2 365 935 • BMW 83 21 2 405 097 • BMW 83 21 2 405 666

Technical data

Viscosity SAE class	0W-30 SAE J300
Density at 15 °C	0,840 g/cm ³ DIN 51757
Viscosity at 40 °C	53,3 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,9 mm ² /s ASTM D 7042-04
Viscosity at -40°C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35°C (CCS)	<= 6200 mPas ASTM D 5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	>= 2,9 mPas ASTM D 5481



Technical data

Pour point	-51 °C DIN ISO 3016
Evaporation loss (Noack)	10,9 % ASTM D 5800 B
Flash point	230 °C DIN ISO 2592
Total base number	8,2 mg KOH/g DIN ISO 3771
Sulfate ash	<= 0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049

Areas of application

Due to the low HTHS viscosity, the motor oil may only be used in approved BMW diesel and gasoline engines.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Full effectiveness and protection for the diesel particulate filter only when the product is not mixed.

Available pack sizes

1 l Canister plastic	20777 BOOKLET
4 l Canister plastic	20778 BOOKLET
5 l Canister plastic	20779 BOOKLET
20 l Canister plastic	20772 D-GB-I-E-P
60 l Drum sheet metal	20773 D-GB
205 l Drum sheet metal	20775 D-GB

Product information

PI 18/01/04/2020



Top Tec 6100 0W-30

Our information is based on thorough research and may be considered reliable, although not legally binding.