

Product information

Motorbike Radiator Cleaner

PI 27/17/04/2020



Description

Motorbike Radiator Cleaner is a concentrate for cleaning coolant circuits. Deposits in the cooling/heating system create blockages for heat exchange and also block thermostat valves and control mechanisms. When engine temperatures are too high, the engine runs uneconomically and suffers excessive wear at considerable risk of damage. Motorbike Radiator Cleaner removes deposits containing oil and limescale, and ensures that the engine runs reliably and at the optimum temperature. Does not contain aggressive acids or alkalis.



The treated product contains biocides as protective agents. Contains a mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

Properties

- disperses sludge
- removes oil and grease-based contaminants
- compatible with antifreezes
- chemical conversion of lime
- neutralizes acids
- neutral behavior in contact with rubber and plastics

Technical data

| | |
|--------------------------------|-----------------------------------|
| Form | flüssig / liquid |
| Color / appearance | hellgelb / light yellow |
| Hazard class as per German VbF | keine / none |
| pH value | ~8,7 |
| Solubility in water | löslich / soluble |
| Odor | charakteristisch / characteristic |
| Density at 20 °C | 1,029 g/cm ³ |

Available pack sizes

| | |
|------------------------|------------------|
| 150 ml Can sheet metal | 3042 D-GB-E |
| 150 ml Can sheet metal | 5923 D-F-I-GR |

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

Suitable for all coolant circuits. Compatible with all conventional coolant additives and antifreezes.

Application

LIQUI MOLY recommends adding Motorbike Radiator Cleaner to the cooling water if problems arise or before changing the coolant. Depending on the level of contamination, run the engine at operating temperature for 10-30 minutes. Drain the cleaner and flush out the cooling system with water. Fill the cooling system according to the manufacturer's instructions. Contents of can are sufficient to treat 5 liters of coolant.

Comment

Store free of frost.