

Product information

Motorbike Fork Oil 5W light

PI 21/09/01/2018



Description

Full synthetic fork oil and shock-absorber oil. Reduces shear losses and provides sure handling performance even after long use. Prevents foam formation and seal hardening. Good corrosion and wear protection provide long service life.

Properties

- lasting corrosion protection
- prevents foam formation
- increases driving safety
- high wear resistance
- prevents seals from swelling

Technical data

Density at 15 °C	0,825 g/cm ³ DIN 51757
Viscosity at 40 °C	18,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	4,1 mm ² /s ASTM D 7042-04
Viscosity index	131 DIN ISO 2909
Pour point	-72 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, autocycles and other two-wheel vehicles.

Application

Follow the instructions of the telescopic fork, shock absorber and two-wheel vehicle manufacturers.



Available pack sizes

500 ml Can plastic	1523 D-GB-I-E-P
500 ml Can plastic	7598 D-RUS-UA
500 ml Can plastic	5950 D-F-I-GR
1 l Can plastic	2716 D-GB-I-E-P
1 l Can plastic	20747 GB-DK-FIN-N-S
1 l Can plastic	20094 GB-F-E-USA-CAN
5 l Canister plastic	1623 D-GB-I-E-P
5 l Canister plastic	5951 D-F-I-GR
20 l Canister plastic	3016 D-GB
205 l Drum sheet metal	20629 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.