

# Product information

## Weld Primer Spray

PI 6/19/05/2017



### Description

Fast drying welding point sealant for inert gas and spot welding operations. The high impact strength allows long-lasting protection to be achieved. The product protects against corrosion between body-work panels. Special pigments ensure very good abrasion resistance on metallic surfaces. Good filling capacity and excellent coverage. Can be overpainted with all standard paint systems (water based, acrylic resin, alkyd resin, epoxy resin).



### Properties

- long-term corrosion protection
- excellent resistance to weathering
- good covering power
- good adhesion
- can be painted over wet-in-wet

### Available pack sizes

400 ml Can aerosol	6000
	D-GB-I-E-P

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Technical data

Propellant	propan / butan
Density at 20 °C	0,765 g/ml
Color / appearance	anthrazit / anthracite
Thermal stability	115 °C
Drying time	15 min Staubtrocken 30-40 min Grifffest
Through-drying	24 h
Shelf life in original sealed container	24 Monate

### Areas of application

For sealing welding points in automotive workshops, accident repairs, automotive construction, welding workshops and locksmith's shops.

### Application

Remove rust, dust and grease thoroughly from the parts to be treated. Sand the substrate down if necessary. Shake can well for 2 minutes. Apply crosswise in several thin layers. The drying time between applications is approx. 5 minutes. **After use, invert the riser pipe and spray head and depress the nozzle until only propellant escapes.**