



600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.

Specifications

- Max. working pressure (bar): 300
- Length (mm): 600
- Temperature (°C): max. 155
- Connection thread: M22 x 1.5
- Weight incl. packaging (kg): 0.7

Compatible Models

- | | |
|--------------------------|--------------------------|
| ◦ HD 13/12-4 St | ◦ HD 9/25 G Classic |
| ◦ HD 5/11 Cage Classic | ◦ HDC Advanced |
| ◦ HD 6/15 G Classic | ◦ HDC Classic |
| ◦ HD 6/15-4 Classic | ◦ HDC Standard |
| ◦ HD 7/11-4 Cage Classic | ◦ HDS 12/14-4 St |
| ◦ HD 7/11-4 Classic | ◦ HDS 12/14-4 St Gas |
| ◦ HD 7/16-4 St | ◦ HDS 12/14-4 St Gas LPG |
| ◦ HD 7/18-4 Classic | ◦ HDS 9/14-4 St |
| ◦ HD 7/20 G Classic | ◦ HDS 9/16-4 St Gas |
| ◦ HD 8/23 G Classic | ◦ HDS 9/20-4 Classic |
| ◦ HD 9/18-4 Cage Classic | ◦ HG 43 |
| ◦ HD 9/18-4 St | ◦ HG 64 |
| ◦ HD 9/20-4 Classic | |
| ◦ | |