



With the new T 10/1 Professional we enlarge our dry vacuum program with a machine made especially for the target group building service contractors. It includes a pluggable power cord (12 m), an antistatic bend, a power cord integration, an extra strong main filter for vacuuming without filter bag and a coloured plug.

Features

The Kärcher T 10/1 Pro Adv Dry Vacuum Cleaner is specially designed for offices and contract cleaners, with pluggable power cable, antistatic bend, cable storage and permanent main filter basket for vacuuming with or without a filter bag. The Kärcher T 10/1 Pro Adv Dry Vacuum Cleaner features a handy antistatic bend with clip system, infinitely variable suction power control, and a large foot switch that enables comfortable, ergonomic vacuuming work that's easier on the back as it minimises time spent bending down. The permanent main filter basket enables cleaning to be performed with or without a filter bag, while the sizeable, outstandingly robust, impact-resistant container features an all-round bumper that protects furniture and other possessions against damage. The 12-metre long, pluggable power cable with its unmistakable yellow plug helps to make any required cable changes easy, quick and cost-efficient. Cable storage on the device head ensures that the cable is stored safely during transport, while the integrated storage keeps all important accessories safe. Included as standard are two long-lasting metal suction tubes (each 0.5 m long), a suction hose, an antistatic bend for reducing electrostatic discharges, a switchable floor nozzle (280 mm) for hard flooring and carpets, and a fleece filter bag.

Large, round, permanent main filter basket made of washable fleece

Extremely strong and dense enough to allow vacuuming for longer times without a filter bag.

Maintenance-friendly

The cable can be replaced quickly and easily by simply loosening 2 screws. This saves time and service costs.

Operation using foot switch

No tedious bending down during everyday work.

Specifications

- Supply voltage (Ph/V/Hz) 1 / 220 - 240 / 50 - 60
- Vacuum (mbar/kPa) 220 / 22
- Air flow (l/s) 43
- Rated performance (W) 700
- Container content (l) 10
- Standard nominal width ID 35
- Cable length (m) 12
- Sound pressure level (dB(A) 57
- Weight without accessories (kg) 5,4
- Weight incl. packaging (kg) 9,2
- Dimensions (L x W x H) (mm) 355 x 310 x 410