



The NT 65/2 Ap is a powerful wet and dry vac with the ApClean system, which ensures constant high suction power and long working intervals. The vacuum features a compact turbine housing with integrated filter cover for easily removing the large flat pleated filter. It is effectively cleaned with the help of the semi-automatic ApClean filter cleaning system. This ensures constant high suction power, longer working intervals and a long service life of the filter. The NT 65/2 Ap features electronic fill level detection for wet vacuuming. It prevents the maximum permitted fill level from being exceeded. The problem-free disposal of vacuumed fluids is made possible by the attached oil-resistant drain hose. Accessories can be quickly and easily connected to the vacuum using the clip system. The unit features a hose storage device, an accessory holder and a large tray e.g. for tools. The required mobility of the NT 65/2 Ap is provided by two large fixed wheels and two guide rolls.

Features

On-board storage

- The large on-board storage space on the casing head ensures that tools and accessories are always stored and close to hand.

Integrated drain hose (oil-resistant)

- Easily accessible drain hose for convenient liquid disposal.

Semi-automatic filter cleaning

- Semi-automatic filter cleaning effectively ensures constant high suction power.

Hose and bend attachment

- Convenient suction hose and bend attachment for easy transport and storage.

Specifications

- Supply voltage (Ph/V/Hz) 1 / 220 - 240 / 50 - 60
- Air flow (l/s) 2 x 74
- Vacuum (mbar/kPa) 254 / 25,4
- Container content (l) 65
- Container material Plastic
- Rated input power (W) max. 2760
- Standard nominal width ID 40
- Cable length (m) 10
- Sound pressure level (dB(A) 73
- Weight without accessories (kg) 20
- Dimensions (L x W x H) (mm) 600 x 480 x 920