



FEATURES

- Quick-action vice for fast workpiece clamping
- Saw bar can be swiveled from 0 ° to 45 ° to allow angled saw cuts
- Easy to read scale for angle adjustment
- Micro switch for automatic limit switch
- Automatic lowering of the saw bar via three-stage adjustable saw bar lowering pressure
- As standard with high-quality bi-metal saw band
- Large, handy handle and low weight allows easy transport to the construction site
- Adjustable material stop for serial work
- Fully equipped machine; The user can work productively immediately after commissioning
- Transport safety

SPECIFICATIONS

- Cutting Capacities:
 - 0° Round (Full Material): 100 mm
 - 0° Quadratic (Full Material): 100 mm
 - 0° Rectangle Horizontal (Full Material): 100 x 150 mm
 - +45° Round (Full Material): 65 mm
 - +45° Quadratic (Full Material): 60 mm
 - +45° Rectangle Horizontal (Full Material): 60 x 100 mm
- Dimensions and Weight:
 - Max. Length: 950 mm
 - Max. Width/Depth: 660 mm
 - Max. Height: 820 mm
 - Length: Approx. 850 mm
 - Width/Depth: Approx. 300 mm
 - Height: Approx. 680 mm
 - Weight: Approx. 23 kg
- Electrical Data:
 - Supply Voltage: 230 V
 - Mains Frequency: 50 Hz
- Machine Data:
 - Saw Band Speed: 45 m/min
 - Saw Band Length: 1470 mm
 - Saw Band Width: 13 mm
 - Saw Band Thickness: 0.65 mm
 - Cutting Angle: 0 – 45°
 - VPE: 1 (Quantity per package)