



FEATURES

- Bench drills and upright drilling machines with gear
- High true running accuracy due to hardened and ground main spindle
- Wide speed range
- Heavy, solid cast iron construction
- Adjustable drilling depth stop with millimetre scale
- Low maintenance gear with grease lubrication

SPECIFICATIONS

- Electrical Connection: 400 V / 3 Ph ~ 50 Hz
- Total Connected Load: 1.5 / 2.2 kW
- Motor Coolant Pump: 40 W
- Drilling Capacity in Steel (S235JR): 30 mm
- Continuous Drilling Capacity in Steel: 26 mm
- Throat Depth: 285 mm
- Spindle Stroke: 125 mm
- Spindle Seat: MT 4
- Automatic Spindle Sleeve Feed: 0.1 / 0.15 / 0.2 mm
- Spindle Speeds: 75 – 2,000 min⁻¹ (8 steps)
- Table Work Surface (L x W): 400 x 420 mm
- T-Slot Size: 14 mm, diagonal
- Rotatable Drilling Table: 360 degrees
- Max Distance Spindle – Table: 820 mm
- Max Distance Spindle – Stand: 1,270 mm
- Stand Work Surface (L x W): 420 x 644 mm
- Stand T-Slot Size: 14 mm
- Number of T-Slots on Stand: 2
- T-Slot Distance on Stand: 150 mm
- Column Diameter: 115 mm
- Dimensions: 725 x 450 x 2,200 mm
- Total Weight: 312 kg