



FEATURES

- Bench drills and upright drilling machines with gear
- High true running accuracy due to hardened and ground main spindle
- Wide speed range
- Heavy, solid cast iron construction
- Adjustable drilling depth stop with millimetre scale
- Low maintenance gear with grease lubrication

SPECIFICATIONS

- Electrical Connection: 400 V / 3 Ph ~ 50 Hz
- Total Connected Load: 1.1 / 1.5 kW
- Drilling Capacity in Steel (S235JR): 24 mm
- Continuous Drilling Capacity in Steel (S235JR): 21 mm
- Throat Depth: 235 mm
- Spindle Stroke: 127 mm
- Spindle Seat: MT 3
- Automatic Spindle Sleeve Feed: No
- Spindle Speeds: 8 Steps, 75 – 2,900 min⁻¹
- Table Work Surface (L x W): 380 x 380 mm
- Inclinal Drilling Table: No
- Rotatable Drilling Table: 360 degrees
- Max Distance Spindle – Table: 450 mm
- Max Distance Spindle – Stand: 610 mm
- Stand Work Surface (L x W): 350 x 322 mm
- Stand T-Slot Size: 14 mm
- Number of T-Slots on Stand: 2
- T-Slot Distance on Stand: 120 mm
- Column Diameter: 92 mm
- T-Slot Size: 14 mm, diagonal
- Dimensions: 600 x 380 x 1,300 mm
- Total Weight: 158 kg