

DQ14



FEATURES

- Separate emergency stop stop switch
- Measurement scale for drilling depth
- Drilling table $\pm 45^\circ$ inclinable and 360° rotatable
- One-piece die-cast aluminium quill lever with soft-grip handles
- Precision spindle drilling
- Safety electrics in 24 V DC voltage
- Guaranteed concentricity accuracy of less than 0.03 mm measured in the drilling sleeve
- Drilling spindle with preprecision ball bearings
- High-quality quick-action drill chuck
- GATES quality belt
- Largely dimensioned base plate with T-slots, heavily ribbed on the rear side

SPECIFICATIONS

- | | |
|---|--|
| • Dimensions and Weight | • Max. Distance from Spindle to Drilling Table: 250 mm |
| • Column Diameter: 46 mm | • Electrical Specifications |
| • Length: Approx. 472 mm | • Drive Motor Power: 0.35 kW |
| • Width/Depth: Approx. 283 mm | • Supply Voltage: 230 V |
| • Height: Approx. 634 mm | • Mains Frequency: 50 Hz |
| • Weight: Approx. 18.5 kg | • Machine Base |
| • Drilling Performance | • Max. Distance from Spindle to Machine Base: 340 mm |
| • Max. Drilling Diameter (Steel, S235JR): 13 mm | • Work Area Length: 138 mm |
| • Continuous Drilling Diameter (Steel, S235JR): 12 mm | • Work Area Width: 128 mm |
| • Drilling Table | • Speed Range |
| • Workspace Length: 170 mm | • Speed Range: 700 – 2500 rpm |
| • Workspace Width: 170 mm | • Number of Gears: 5 Steps |
| • T-Groove Type: Diagonal | • Spindle |
| • T-Groove Size: 14 mm | • Quill Stroke: 52 mm |
| • Number of T-Grooves: 2 | • Spindle Chuck: Solid/B16 |
| • Rotation: 360° | • Reach: 104 mm |
| • Angle: $\pm 45^\circ$ | • Packaging |
| • Load Bearing Capacity: 8 kg | • VPE (Units per Package): 1 |