365534

DIGITAL METERED CONTROL VALVE, EC30 SERIES, 30 L/MIN, FLEXIBLE OUTLET 90° TUBE, QUARTER TURN

SAMOA metered control valves are used at the end of hose assembly for measured dispensing of lubricants and antifreeze solutions.
· Extensively and rigorously field tested. Reliable performance.
· High precision machined measuring chamber with tight tolerances, quality gears and stainless steel shafts eliminate the need of calibration to adjust for fluid viscosity.
· Sealed battery compartment and isolated electronic register for extended life.
· Easy to read large character display, with batch, trip (resettable totalizer) and totalizer functions.
· Rough TPE boot surrounds the entire meter for even greater durability.
· Replaceable AAA batteries.

DATOS TÉCNICOS

Accuracy	0.005
Fluid inlet	1/2" BSP (F)
Fluid outlet	1/2" BSP (F)
Fluids	Gear oil, Coolant, Transmission fluid, Hydraulic oil, Aceite
Maximum free flow delivery	30 l/min
Maximum free flow delivery (SI)	30 l/min, 8 gal/min
Maximum outlet pressure	100 bar (1450 psi)
Meter	Digital
Metric	Litres
Operating Temperature Range	-10 - 60 °C (14 - 140 °F)
Outlet nozzle type	Quarter turn manual
Weight	1.3 kg (2.8 lb)
Wetted materials	Zinc plated steel, NBR, Polyamide, Aluminium, Acetal, TPU, Stainless steel

DOCUMENTACIÓN

NOMBRE	DESCRIPCIÓN
836850.pdf	Instructions manual 3
836847.pdf	Instructions manual 3
836826.pdf	Instructions manual 2
836829.pdf	Instructions manual 1

CUADRO DE MODELOS

365521

Outlet nozzle type	N/A

365532

Outlet nozzle type	Automatic

365534

Outlet nozzle type	Quarter turn manual

365537

Outlet nozzle type	Quarter turn manual

365535

Outlet nozzle type	Automatic

365536

Outlet nozzle type	Quarter turn manual

365538

Outlet nozzle type	Quarter turn narrow manual

SAMOA Industrial, S.A.
Pol. Ind. Porceyo, I-14 · Camino del Fontán, 831 · 33392 Gijón - España
Tel.: (+34) 985 381 488 - Fax: (+34) 985 384 163
info@samoaindustrial.com
www.samoaindustrial.com