

347120
PNEUMATIC PISTON OIL PUMP, PUMPMaster 4, PM4 - 5:1, STUB


PM4 series air operated piston pumps. Double action air operated medium pressure pumps for dispensing lubricants in medium to large size installations, that include multiple outlets with simultaneous operation. Pumps include height adjustable 2" BSP (M) bung adaptor for drum and tank bung mounting. Built in port for optional pressure relief valve (PN 609 007). Air consumption with 6 bar (87 psi) air inlet pressure and 10 l/min (2.6 gal/min). Maximum free delivery at 7 (102 psi) bar. Maximum noise level measured at 1 m (3') from the pump, 7 bar (102 psi) air pressure and free delivery.

DATOS TÉCNICOS

Air consumption	400 NL/min (14 scfm)
Air inlet	3/8" NPSM (F)
Air motor effective diameter	60 mm (2.4 ")
Air motor stroke	100 mm (4 ")
Air pressure operating range	1.5 - 10 bar (21.75 - 145 psi)
Cycles per minute (aprox.)	125 cycles
Delivery	10 l/min (2.7 gal/min)
Delivery per cycle	10 l (2.7 gal)
Fluid inlet	1" BSP (F)
Fluid inlet type	Ball check
Fluid outlet	3/4" NPSM (F)
Fluids	Gear oil, Aceite, Hydraulic oil, Transmission fluid
Maximum free flow delivery (SI)	25 l/min, 6.6 gal/min, 25 l/min
Maximum outlet pressure	50 bar (700 psi)
Noise level	95 dB
Pressure ratio	5:1
Pump mounting	Universal stub pump
Total height	663 mm (26 ")
Tube height	278 mm (10.9 ")
Weight	5.6 kg (12.3 lb)
Wetted materials	PTFE, NBR, Aluminium, Polyurethane, Steel



DOCUMENTACIÓN
NOMBRE

834809.pdf

DESCRIPCIÓN

Instructions manual 1

+ INFO



CUADRO DE MODELOS

347120

Pump mounting	Universal stub pump
Tube height	278 mm (10.9 ")
Total height	663 mm (26 ")

348120

Pump mounting	205 l (55 gal) drum bung mounted
Tube height	915 mm (36 ")
Total height	1300 mm (51.2 ")