

Coolant Ready Mix RAF 11

Description

Ready-to-use mixture based on ethylene glycol. The antifreeze contains no amines, nitrites or phosphates and offers ideal protection from frost, rust and overheating through its special inhibitor formulation. This therefore provides reliable vehicle performance all year round.

LIQUI MOLY recommends this radiator antifreeze for vehicles that require a product with the following manufacturers' approvals:

Alfa Romeo 9.55523
Audi TL-774 C = G11
Behr
BMW GS 94000
Chrysler MS-7170
CUMMINS 85T8-2
Deutz DQC CA-14
Fiat 9.55523
Iveco Standard 18-1830
Jl Case JIC-501
Lada/AVTOVAZ TTM VAZ 1.97.717-97
Lancia 9.55523
MAN 324 Typ NF
MTU MTL 5048
Opel/GM GME L46014
Perkins
Porsche TL-774 C = G11
Saturn
Seat TL-774 C = G11
Skoda TL-774 C = G11
Toyota Motor Corporation
Vauxhall GMEL1301
Volkswagen TL-774 C = G11
Volvo Cars 128 6083 / 002
Volvo Construction
Volvo Trucks

as well as for vehicles that require a radiator antifreeze of this quality.

Properties

- prevents operational malfunctions
- contains no amines, nitrites or phosphates
- ready for use
- outstanding corrosion protection
- provides outstanding protection against overheating
- prevents the cooling system from freezing up
- for extended change intervals (note manufacturer's instructions)

Technical data

Frost and overheating protection -20 bis +104 / -20 to +104 °C

Technical data

Base	Ethylenglykol mit Inhibitoren / ethylene glycol with inhibitors
Density at 20 °C	1,05 g/cm ³
Color / appearance	blau / blue
Flash point	> 100 °C
Shelf life in original sealed container	60 months

Areas of application

Suitable for all cooling systems and engines (including aluminium engines) in passenger vehicles, commercial motor vehicles, buses, agricultural machinery and stationary engines/machines where coolant system protection of this quality is required.

Application

Clean the coolant system with Radiator Cleaner (part no. 3320). Empty the coolant system, rinse thoroughly with water and fill with Coolant Ready Mix RAF11. Disposal is made according to the local regulations. The change intervals vary according to the manufacturer's instructions. Coolant Ready Mix RAF11 is mixable and compatible with radiator antifreeze containing silicates according to VW standard G11 – TL 774-C (LIQUI MOLY Radiator Antifreeze RAF11) or original silicate-free radiator antifreeze according to VW standard TL 774-D/F (LIQUI MOLY Radiator Antifreeze RAF12 Plus or LIQUI MOLY Coolant Ready Mix RAF12 Plus).

Available pack sizes

1 l Bottle plastic	20660 D-GB-I-E-P
5 l Canister plastic	8809 D-GB-I-E-P
20 l Canister plastic	8822 D-GB
200 l Drum sheet metal	8823 D-GB



Product information

PI 18/09/11/2018

Coolant Ready Mix RAF 11



Our information is based on thorough research and may be considered reliable, although not legally binding.