

363115
CONTROL VALVE, PA40 SERIES, 40 L/MIN, FLEXIBLE OUTLET 90° TUBE, AUTOMATIC


SAMOA control valves are used at the end of hose assembly to dispense lubricants and antifreeze solutions.

- Extensively and rigorously field tested. Reliable performance.
- Aluminium body with light weight ergonomic design. Soft grip valve for comfort.
- Cam and piston valve design for minimum flow resistance.
- Large inlet swivel and inlet filter with large screen surface.
- Swivel and outlet covers.
- Safety latch must be depressed before product can be dispensed. Trigger can be locked open for dispensing large volumes.
- Wide selection of outlets available.

DATOS TÉCNICOS

Accuracy	-
Fluid inlet	1/2" BSP (F)
Fluid outlet	1/2" BSP (F)
Fluids	Coolant, Hydraulic oil, Gear oil, Transmission fluid, Aceite
Maximum free flow delivery	40 l/min
Maximum free flow delivery (SI)	10.57 gal/min, 40 l/min
Maximum outlet pressure	100 bar (1450 psi)
Meter	N/A
Metric	-
Operating Temperature Range	-10 - 70 °C (14 - 160 °F)
Outlet nozzle type	Automatic
Weight	0.47 kg (1 lb)
Wetted materials	Zinc plated steel, TPU, Polyamide, Aluminium

DOCUMENTACIÓN

NOMBRE	DESCRIPCIÓN
836829.pdf	Instructions manual 1
836850.pdf	Instructions manual 3
836847.pdf	Instructions manual 2
836835.pdf	Instructions manual 3

CUADRO DE MODELOS**363100**

Outlet nozzle type	N/A
--------------------	-----

363114

Outlet nozzle type	Quarter turn manual
--------------------	---------------------

363112

Outlet nozzle type	Automatic
--------------------	-----------

363116

Outlet nozzle type	Quarter turn manual
--------------------	---------------------

363115

Outlet nozzle type	Automatic
--------------------	-----------

363118

Outlet nozzle type	Quarter turn narrow manual
--------------------	----------------------------

363117

Outlet nozzle type	Quarter turn manual
--------------------	---------------------