

413082

**CONTROL VALVE, PG-77/ZF SERIES, 1 KG/MIN, GREASE,
REINFORCED HOSE OUTLET, Z-SWIVEL**



High pressure grease control guns with ergonomic body and trigger designed to reduce operator hand fatigue. Manufactured in aluminium with steel insert for high pressure. With z-swivel and 450 mm double steel braid reinforced rubber hose with 3 jaw connector

DATOS TÉCNICOS

Accuracy	-
Fluid inlet	1/4" BSP (F)
Fluid outlet	1/8" BSP (F)
Fluids	Grease
Maximum free flow delivery	1 kg/min
Maximum free flow delivery (SI)	2.2 lb/min, 1 kg/min
Maximum outlet pressure	500 bar (7250 psi)
Meter	N/A
Metric	-
Operating Temperature Range	-10 - 70 °C (14 - 160 °F)
Outlet nozzle type	Grease connector
Weight	1.21 kg (2.66 lb)
Wetted materials	Rubber, Steel, Zinc plated steel

DOCUMENTACIÓN

NOMBRE

841801.pdf

DESCRIPCIÓN

Instructions manual 1

CUADRO DE MODELOS

413077

Outlet nozzle type	Grease connector
--------------------	------------------

413080

Outlet nozzle type	Grease connector
--------------------	------------------

413082

Outlet nozzle type	Grease connector
--------------------	------------------

413081

Outlet nozzle type	Grease connector
--------------------	------------------