

366060

## HIGH VOLUME IN-LINE DIGITAL METER, C70 SERIES, 3/4", 80 L/MIN, ALUMINIUM



Oval gear meter for use as in-line meters with oil or diesel. It can be wall mounted in the fluid line or at the pump outlet. Meter includes an electronic register controlled by wetted magnets and powered with two AAA alkaline batteries. It is shock proof and isolated from the fluid handled and the display is multi- function, showing the volume dispense per delivery and has a permanent and a resettable (trip function) totalizers. The display can be programmed to show delivery in litres, quarts, pints and US gallons. The assembly is enclosed in TPE moulded shroud. It can also be set to show the flow rate in units of measure per minute.

### DATOS TÉCNICOS

Accuracy	0.005
Flow range	8 - 80 l/min (2.1 - 21 gal/min)
Fluid inlet	3/4" BSP (F)
Fluid outlet	3/4" BSP (F)
Fluids	Coolant, Aceite, Hydraulic oil, Gear oil, Transmission fluid
Maximum free flow delivery	80 l/min (21.1 gal/min)
Maximum outlet pressure	100 bar (1450 psi)
Meter	DIGITAL
Metric	LITRES
Operating Temperature Range	-10 - 60 °C (14 - 140 °F)
Pulses per litre	109
Weight	0.8 kg (1.76 lb)
Wetted materials	Aluminium, LCP, NBR, Stainless steel

### DOCUMENTACIÓN

#### NOMBRE

836845.pdf

#### DESCRIPCIÓN

Instructions manual 1