


366000
IN-LINE DIGITAL METER, C30 SERIES, 1/2", 30 L/MIN, ALUMINIUM


Oval gear meters for use as in-line meters with oil, DEF / AdBlue®, windshield wash solution or antifreeze solution, depending on the meter wetted materials. They can be wall mounted in the fluid line or at the pump outlet. Meters include an electronic register controlled by wetted magnets and powered with two AAA alkaline batteries. It is shock proof and isolated from the fluid handled. Meter display is multi-function, showing the volume dispensed per delivery, and has a permanent and a resettable (trip function) totalizers. The display can be programmed to show delivery in litres, quarts, pints and US gallons. The assembly is enclosed in TPE moulded shroud.

DATOS TÉCNICOS

Accuracy	0.005
Flow range	1 - 30 l/min (0.26 - 8 gal/min)
Fluid inlet	1/2" BSP (F)
Fluid outlet	1/2" BSP (F)
Fluids	Gear oil, Transmission fluid, Aceite, Hydraulic oil
Maximum free flow delivery	30 l/min (8 gal/min)
Maximum outlet pressure	100 bar (1450 psi)
Meter	DIGITAL
Metric	LITRES
Operating Temperature Range	-10 - 60 °C (14 - 140 °F)
Pulses per litre	164
Weight	0.53 kg (1.17 lb)
Wetted materials	Aluminium, Stainless steel, LCP, NBR

DOCUMENTACIÓN

NOMBRE	DESCRIPCIÓN
836826.pdf	Instructions manual 1