

504351
**HEAVY DUTY HOSE REEL, RM-12L SERIES, 15 M, 3/8",
GREASE / HYDRAULIC OIL**


Non contractual picture

Very tough construction able to stand regular use and abuse in Intensive Duty applications. Fatigue resistant steel spring for years of durable performance and even load when pulling and recoiling the hose. Full port shaft and swivel for no restrictions. Spool mounted on two permanent lubricated and sealed ball bearings to reduce torque load on spring for smooth retraction and longer life. Large effective radial latching area for easier operation. Hose guide arm can be placed in different positions to accommodate any method of mounting. Narrow footprint allows accommodating more reels on the same surface. Hose reels with hose include 0,8 m inlet hose.

Model with 15 m 3/8" hose for GREASE / HYDRAULIC OIL.

DATOS TÉCNICOS

Bare reel part number	504359
Fluid inlet	3/8" BSP (M)
Fluid outlet	1/4" BSP (M)
Fluids	Hydraulic oil, Grease
Hose in diameter	3/8"
Hose length	15 m (49.21 ft)
Installation options	Floor, Wall, Tank, Ceiling
Weight	26 kg (57.3 lb)
Working Pressure	4060 psi, 280 bar, 280 bar


DOCUMENTACIÓN
NOMBRE
DESCRIPCIÓN

850836.pdf

Instructions manual 1

836823.pdf

Instructions manual 2

+ INFO


CUADRO DE MODELOS**504250**

Weight	24 kg (53 lb)
Hose in diameter	1/2"
Hose length	15 m (49.21 ft)

504150

Weight	24 kg (53 lb)
Hose in diameter	1/2"
Hose length	15 m (49.21 ft)

504351

Weight	26 kg (57.3 lb)
Hose in diameter	3/8"
Hose length	15 m (49.21 ft)

504350

Weight	27.5 kg (60.6 lb)
Hose in diameter	1/4"
Hose length	15 m (49.21 ft)

504450

Weight	26 kg (57.3 lb)
Hose in diameter	3/8"
Hose length	15 m (49.21 ft)