

504250

## HEAVY DUTY HOSE REEL, RM-12L SERIES, 15 M, 1/2", LUBRICANT OIL



Non contractual picture

Very tough construction able to stand regular use and abuse in Intensive Duty applications. Fatigue resistant steel spring for years of durable performance and even load when pulling and recoiling the hose. Full port shaft and swivel for no restrictions. Spool mounted on two permanent lubricated and sealed ball bearings to reduce torque load on spring for smooth retraction and longer life. Large effective radial latching area for easier operation. Hose guide arm can be placed in different positions to accommodate any method of mounting. Narrow footprint allows accommodating more reels on the same surface. Hose reels with hose include 0,8 m inlet hose.  
Model with 15 m 1/2" hose for LUBRICANT OIL.

### DATOS TÉCNICOS

Bare reel part number	504259
Fluid inlet	1/2" BSP (M)
Fluid outlet	1/2" BSP (M)
Fluids	Aceite
Hose in diameter	1/2"
Hose length	15 m (49.21 ft)
Installation options	Tank, Floor, Wall, Ceiling
Weight	24 kg (53 lb)
Working Pressure	160 bar, 2320 psi, 160 bar

### DOCUMENTACIÓN


#### NOMBRE

836823.pdf  
850836.pdf

#### DESCRIPCIÓN

Instructions manual 2  
Instructions manual 1

### + INFO



**CUADRO DE MODELOS**

**504250**

Weight	24 kg (53 lb)
Hose in diameter	1/2"
Hose length	15 m (49.21 ft)

**504150**

Weight	24 kg (53 lb)
Hose in diameter	1/2"
Hose length	15 m (49.21 ft)

**504351**

Weight	26 kg (57.3 lb)
Hose in diameter	3/8"
Hose length	15 m (49.21 ft)

**504350**

Weight	27.5 kg (60.6 lb)
Hose in diameter	1/4"
Hose length	15 m (49.21 ft)

**504450**

Weight	26 kg (57.3 lb)
Hose in diameter	3/8"
Hose length	15 m (49.21 ft)